

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of ESLAM SERIE RS30 — PTFE Casting Film — PTFE Glass Fabric — PTFE Casting Film

Product	Product Category	Coating
PTFE CAST FILM	ESLAM SERIE	MULTILAYER
LAMINATED GLASS FABRIC	ESLAM SERIE	PTFE CAST FILM

Properties	Metric		Imperial	
Standard width Please ask for other widths	700, 1200 mm		27.6, 47.3 inches	
Thickness	0.30 mm		0.0118 inches	
Color	Red / Black		Red / Black	
Weight	600 g/m²		17.70 oz/yd²	
PTFE content	67%		67%	
Tensile Stength	485 N/cm	Warp	277.1 lbs/inches	Warp
	468 N/cm	Fill	267.4 lbs/inches	Fill
Temperature resistance	-73 to +260 °C		-100 to +500 °F	

ESONE® ESLAM RS30 is a multilayer PTFE cast film laminated glass fabric. The surface of ESLAM series is crack free and pinhole free, which prevents oil and fat penetration to substrate, and is outstanding resistant to bacteria contamination.

ESLAM are increasingly replacing traditional PTFE coated fabric since the better performance in release property, oil resistant property, glossy surface, easy to clean property, mechanical strength and others. ESONE ESLAM PTFE film laminated belts is widely used for contacting grill machines(such as Formcook, Berief and CFS Twingrill), chemical industry, aerospace industry and so on.















ESONE® is a registered trademark owned by
Jiangsu Esone New Material Co.,Ltd
Taixing Youngsun FL-Plastics Co.,Ltd
Western End of South Third Ring Road, Taixing, Jiangsu, China
Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com