

ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of ANTI STATIC SERIE YS7025BJ

Product	Product Category	Coating
PTFE GLASS FABRIC SELF ADHESIVE	ANTI STATIC SERIE	SILICONE PRESSURE SENSITIVE ADHESIVE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1250, 1500 mm	39.5, 49.3, 59 inches
Backing thickness PTFE Glass	0.25 mm	0.0099 inches
Total Thickness PTFE Glass and Silicone PSA	0.30 mm	0.0119 inches
Backing weight PTFE Glass	530 g/m ²	15.63 oz/yd ²
Tensile Strength	460 N/cm Warp	263 lbs/inches Warp
	400 N/cm Fill	229 lbs/inches Fill
Adhesion	6.0 N/cm	55 oz/inches
Surface resistance	10 ⁷ to 10 ⁵ OHMS/m ²	10 ⁷ to 10 ⁵ OHMS/m ²
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® Anti-static Series PTFE coated fiberglass fabric with Silicone PSA, has easy release surface, can continuous working from -73 to +260 °C and is conductive(Anti-static). It's widely used in applications such as release adhesive tape for form fill, impulse/L-bar, polybag sealing and heat press machines, covering drying cylinders, wire and cable insulation and protection for LCD/FPC/PCB industry, non stick roll coverings for printing and textile, PVC window laminating, composit mold release and bonding.



ESONE® is a registered trademark owned by
 Jiangsu Esone New Material Co.,Ltd
 Taixing Youngsun FL-Plastics Co.,Ltd
 Western End of South Third Ring Road, Taixing, Jiangsu, China
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com